




Suitable for ceiling, wall or pendant mounting using suspension system. Specially fabricated to incorporate a built-in camlock or padlock. Prevention against pilferage or any acts of vandalism. The wire guard is hinged on one side of the casing of easy maintenance and installation. Discrete appearance achieved with adjustable lampholder. Cover plate held securely by treaded nut, offering large screw area using hand for fast installation. Public hallways, staircases, corridors and lift lobbies.



Technical Data

Body	Made of heavy gauge sheet steel.
Guard	Heavy gauge galvanized steel epoxy powder coated.
Paintwork	Fully coated with a high gloss white epoxy polyester powder, giving resilient finish.
Light Source	Fluorescent TL-5 lamp of 28 W.
Electrical Data	240V, 50Hz, Power factor 0.95.
Wire	HR 105° C.
Ballast	Electronic Ballast.
Lampholder/ Starterholder	Moulded from Polycarbonate Material.
Optional Components	Fused terminal block/Emergency pack.

Dimensions

MODEL NO.	NO. OF LAMP	L(MM)	L1(MM)	W(MM)	W1(MM)	H(MM)	H1(MM)
SWG 128 (Cam)	1x28W	1171	-	100	-	43	115
SWG 228 (Cam)	2x28W	1171	-	100	-	43	115



Note : Subject to +/- 1.5mm

*SJ Lite reserves the right to change and amend the specification without prior notice.