





Fixed recessed downlight for halogen lamp. Suitable for offices, commercial halls, museums, galleries, exhibitions, etc.



TM5 Utilization Factors

Utilization factors			LOR =46.3% DLOR =46.3% ULOR =0.0%								
Room reflection			Room index								
C	W	F	0.75	1	1.25	1.5	2	2.5	3	4	5
0.7	0.5	0.2	39	42	44	45	47	48	49	50	51
	0.3		37	40	42	44	46	47	48	49	50
0.5	0.1	0.2	36	39	41	42	44	46	47	48	49
	0.5		39	42	43	44	46	47	48	48	49
0.3	0.3	0.2	37	40	42	43	45	46	47	48	48
	0.1		36	39	40	42	44	45	46	47	48
0.0	0.5	0.2	38	41	42	43	45	46	46	47	47
	0.3		37	39	41	42	44	45	45	46	47
0.0	0.1	0.0	36	38	40	41	43	44	45	46	46
	0.0		35	37	39	40	41	42	43	44	44
			SHR NOM =0.75		SHR MAX =0.98			SHR MAX			
			TR =0.98								



Technical Data

Photometry constructed by own Goniophotometer accurately measure the intensity distribution LOR, photometric factors and lumen per watt of light fittings.

Body & Ring	Made of compress cold rolled steel.
Reflector	Anodised Aluminium.
Paintwork	Coated with a high gloss white epoxy polyester powder, giving resilient finish.
Light Source	Halogen bulb 35W/50W.
Electrical Data	240V, 50Hz
Transformer	12V 35W/50W
Lampholder	GU5.3
Optional Light Source	LED MR16 is compatitble and replaceable.

Dimensions

Ø110 H45(MM)

MODEL NO.	COLOR
PLUTO 808.035	WHITE
PLUTO 808.035	SILVER

MODEL NO.	COLOR
PLUTO 808.050	WHITE
PLUTO 808.050	SILVER



Note : Subject to +/- 1.5mm

*SJ Lite reserves the right to change and amend the specification without prior notice.