




Suitable for ceiling or pendant mounting with suspension system. Mirror reflector held securely by treaded nut, offering large screw area using hand for fast installation. Allow a wide and efficient distribution of light. End to end continuously mounting from performed punch out type without additional drilling required. Recommended for use where lighting needs to be concentrated on certain areas.



Technical Data

Body	Made of heavy gauge sheet steel.
Reflector	Aluminum Reflector.
Paintwork	Fully coated with a high gloss white epoxy polyester powder, giving resilient finish.
Light Source	Fluorescent T5 28W.
Electrical Data	240V, 50Hz, Power factor 0.95.
Wire	HR 105° C.
Ballast	Polyester Vacuum Impregnated.
Condenser	Metallised Polypropylene Film.
Starter	SERIES(4W-22W), SINGLE(4W-80W).
Lampholder/ Starterholder	Moulded from Polycarbonate Material.
Optional Component	Fused terminal block/Electronic ballast/Emergency packs.
Optional Light Source	** SJ Lite LED Tube is compatible and replaceable (Not compatible for ECG/Emergency fitting).

**Request for advise if install other brand of LED tube.

Dimensions

MODEL NO.	NO. OF LAMP	L(MM)	L1(MM)	W(MM)	W1(MM)	H(MM)	H1(MM)
SB 228 (M Type)	2x28W	1168	-	150	-	38	69



Note : Subject to +/- 1.5mm

*SJ Lite reserves the right to change and amend the specification without prior notice.