





ECO SWG T8 Vandal Proof Batten Series

Features

Specially fabricated to incorporate a built-in camlock or padlock. Prevention against pilferage or any acts of vandalism. The wire guard is hinged on one side of the casing of easy maintainance and installation. Discrete appearance achieved with adjustable lampholder. Cover plate held securely bu treaded nut, offering large screw area using hand for fast installation.

Luminaire Product Description

Mounting	Surface
Housing & Guard Material	Cold Roll Steel
Coating	Epoxy Polyester Powder
Light Source	SJLITE ECO Glass Tube HO
Input Voltage	240V~, 50Hz
Power Factor	>0.9
Ingress Protection	IP20
Insulation Classification	Class I


Control



Application


Ideal for car parks, staircase, loading bays, corridors and lift lobbies.

Wiring Diagram





Dimension



Order Reference

Model	Quantity Of Tube	Length Of Tube	Example:
ECO SWG	1 2	A (2ft) C (4ft)	ECO SWG 1A 120 — ECO SWG 1 A 1 20 Length Of Tube Quantity Of Tube Quantity Of Tube Quantity Of Tube

Order Information

Model No.	No. Of Lamp	L(mm)	L1(mm)	W(mm)	W1(mm)	H(mm)	H1(mm)
ECO SWG 1A 120	1	616	616 629	54	81	37	109
ECO SWG 2A 220	2			100	105	45	115
ECO SWG 1C 140	1	1224	1233	54	81	37	109
ECO SWG 2C 240	2		1233	100	105	45	115

Note : Subject to +/- 1.5mm

*Other various types are available upon request.