Cable Ladder
System

Cable ladder is system component used for cable support consisting of supporting side members, fixed to each other by means of rungs. Cable ladder is typically of stronger built and able to carry more load. The configuration is easy thus less accessories are required. One of the design advantages is it can get cable drops through the rungs and an extra riser is not required.

Cable Ladder Profile

Cable Ladder System

Cable Ladder Straight "Type Z" (Welded / Knock Down)

Optional Accessories

Vertical Adjustable Join

"Type Z"

Dimension in Millimeter (mm)

L : Length
W : Width
H : Height

Cable Ladder "Type Z" - Welded (WD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/Z-(150X50)-WD	2438 / 3000 x 150 x 50	49	2
SCL/Z-(200X50)-WD	2438 / 3000 x 200 x 50	49	2
SCL/Z-(250X50)-WD	2438 / 3000 x 250 x 50	49	2
SCL/Z-(300X50)-WD	2438 / 3000 x 300 x 50	49	2
SCL/Z-(150X75)-WD	2438 / 3000 x 150 x 75	74	2
SCL/Z-(200X75)-WD	2438 / 3000 x 200 x 75	74	2
SCL/Z-(250X75)-WD	2438 / 3000 x 250 x 75	74	2
SCL/Z-(300X75)-WD	2438 / 3000 x 300 x 75	74	2
SCL/Z-(450X75)-WD	2438 / 3000 x 450 x 75	74	2
SCL/Z-(600X75)-WD	2438 / 3000 x 600 x 75	74	2
SCL/Z-(900X75)-WD	2438 / 3000 x 900 x 75	74	2
SCL/Z-(150X100)-WD	2438 / 3000 x 150 x 100	99	2
SCL/Z-(200X100)-WD	2438 / 3000 x 200 x 100	99	2
SCL/Z-(250X100)-WD	2438 / 3000 x 250 x 100	99	2
SCL/Z-(300X100)-WD	2438 / 3000 x 300 x 100	99	2
SCL/Z-(400X100)-WD	2438 / 3000 x 400 x 100	99	2
SCL/Z-(450X100)-WD	2438 / 3000 x 450 x 100	99	2
SCL/Z-(500X100)-WD	2438 / 3000 x 500 x 100	99	2
SCL/Z-(600X100)-WD	2438 / 3000 x 600 x 100	99	2
SCL/Z-(750X100)-WD	2438 / 3000 x 750 x 100	99	2
SCL/Z-(900X100)-WD	2438 / 3000 x 900 x 100	99	2
SCL/Z-(1000X100)-WD	2438 / 3000 x 1000 x 100	99	2
SCL/Z-(200X125)-WD	2438 / 3000 x 200 x 125	124	2
SCL/Z-(250X125)-WD	2438 / 3000 x 250 x 125	124	2
SCL/Z-(300X125)-WD	2438 / 3000 x 300 x 125	124	2
SCL/Z-(400X125)-WD	2438 / 3000 x 400 x 125	124	2
SCL/Z-(450X125)-WD	2438 / 3000 x 450 x 125	124	2
SCL/Z-(500X125)-WD	2438 / 3000 x 500 x 125	124	2
SCL/Z-(600X125)-WD	2438 / 3000 x 600 x 125	124	2
SCL/Z-(750X125)-WD	2438 / 3000 x 750 x 125	124	2
SCL/Z-(900X125)-WD	2438 / 3000 x 900 x 125	124	2
SCL/Z-(1000X125)-WD	2438 / 3000 x 1000 x 125	124	2
SCL/Z-(200X150)-WD	2438 / 3000 x 200 x 150	149	2
SCL/Z-(250X150)-WD	2438 / 3000 x 250 x 150	149	2
SCL/Z-(300X150)-WD	2438 / 3000 x 300 x 150	149	2
SCL/Z-(400X150)-WD	2438 / 3000 x 400 x 150	149	2
SCL/Z-(450X150)-WD	2438 / 3000 x 450 x 150	149	2
SCL/Z-(500X150)-WD	2438 / 3000 x 500 x 150	149	2
SCL/Z-(600X150)-WD	2438 / 3000 x 600 x 150	149	2
SCL/Z-(750X150)-WD	2438 / 3000 x 750 x 150	149	2
SCL/Z-(900X150)-WD	2438 / 3000 x 900 x 150	149	2
SCL/Z-(1000X150)-WD	2438 / 3000 x 1000 x 150	149	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

Cable Ladder System

Cable Ladder Straight "Type Z" (Welded / Knock Down)

Cable Ladder "Type Z" - Knock Down (KD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/Z-(150X50)-KD	2438 / 3000 x 150 x 50	49	2
SCL/Z-(200X50)-KD	2438 / 3000 x 200 x 50	49	2
SCL/Z-(250X50)-KD	2438 / 3000 x 250 x 50	49	2
SCL/Z-(300X50)-KD	2438 / 3000 x 300 x 50	49	2
SCL/Z-(150X75)-KD	2438 / 3000 x 150 x 75	74	2
SCL/Z-(200X75)-KD	2438 / 3000 x 200 x 75	74	2
SCL/Z-(250X75)-KD	2438 / 3000 x 250 x 75	74	2
SCL/Z-(300X75)-KD	2438 / 3000 x 300 x 75	74	2
SCL/Z-(450X75)-KD	2438 / 3000 x 450 x 75	74	2
SCL/Z-(600X75)-KD	2438 / 3000 x 600 x 75	74	2
SCL/Z-(900X75)-KD	2438 / 3000 x 900 x 75	74	2
SCL/Z-(150X100)-KD	2438 / 3000 x 150 x 100	99	2
SCL/Z-(200X100)-KD	2438 / 3000 x 200 x 100	99	2
SCL/Z-(250X100)-KD	2438 / 3000 x 250 x 100	99	2
SCL/Z-(300X100)-KD	2438 / 3000 x 300 x 100	99	2
SCL/Z-(400X100)-KD	2438 / 3000 x 400 x 100	99	2
SCL/Z-(450X100)-KD	2438 / 3000 x 450 x 100	99	2
SCL/Z-(500X100)-KD	2438 / 3000 x 500 x 100	99	2
SCL/Z-(600X100)-KD	2438 / 3000 x 600 x 100	99	2
SCL/Z-(750X100)-KD	2438 / 3000 x 750 x 100	99	2
SCL/Z-(900X100)-KD	2438 / 3000 x 900 x 100	99	2
SCL/Z-(1000X100)-KD	2438 / 3000 x 1000 x 100	99	2
SCL/Z-(200X125)-KD	2438 / 3000 x 200 x 125	124	2
SCL/Z-(250X125)-KD	2438 / 3000 x 250 x 125	124	2
SCL/Z-(300X125)-KD	2438 / 3000 x 300 x 125	124	2
SCL/Z-(400X125)-KD	2438 / 3000 x 400 x 125	124	2
SCL/Z-(450X125)-KD	2438 / 3000 x 450 x 125	124	2
SCL/Z-(500X125)-KD	2438 / 3000 x 500 x 125	124	2
SCL/Z-(600X125)-KD	2438 / 3000 x 600 x 125	124	2
SCL/Z-(750X125)-KD	2438 / 3000 x 750 x 125	124	2
SCL/Z-(900X125)-KD	2438 / 3000 x 900 x 125	124	2
SCL/Z-(1000X125)-KD	2438 / 3000 x 1000 x 125	124	2
SCL/Z-(200X150)-KD	2438 / 3000 x 200 x 150	149	2
SCL/Z-(250X150)-KD	2438 / 3000 x 250 x 150	149	2
SCL/Z-(300X150)-KD	2438 / 3000 x 300 x 150	149	2
SCL/Z-(400X150)-KD	2438 / 3000 x 400 x 150	149	2
SCL/Z-(450X150)-KD	2438 / 3000 x 450 x 150	149	2
SCL/Z-(500X150)-KD	2438 / 3000 x 500 x 150	149	2
SCL/Z-(600X150)-KD	2438 / 3000 x 600 x 150	149	2
SCL/Z-(750X150)-KD	2438 / 3000 x 750 x 150	149	2
SCL/Z-(900X150)-KD	2438 / 3000 x 900 x 150	149	2
SCL/Z-(1000X150)-KD	2438 / 3000 x 1000 x 150	149	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

◄ Flatwise Equal/Unequal Cross

SCL/Z/WD AC-1
SCL/Z/KD AC-1

Flatwise Equal/Unequal Tee ►

SCL/Z/WD AC-2
SCL/Z/KD AC-2

◄ Righthand Reducer

SCL/Z/WD AC-3
SCL/Z/KD AC-3

Lefthand Reducer ►

SCL/Z/WD AC-4
SCL/Z/KD AC-4

**Other design and sizes are available upon request.

"Type Z" - WD/KD

◄ **Straight Reducer**
SCL/Z/WD AC-5
SCL/Z/KD AC-5

Flatwise Elbow ►
SCL/Z/WD AC-6
SCL/Z/KD AC-6

◄ **Edgewise Elbow Left**
SCL/Z/WD AC-7
SCL/Z/KD AC-7

Edgewise Elbow Right ►
SCL/Z/WD AC-8
SCL/Z/KD AC-8

"Type Z" - WD/KD

**Other design and sizes are available upon request.

Optional Accessories

Vertical Adjustable Join

"Type G - Inner "

Cable Ladder "Type G - Inner" - Welded (WD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/G/I-(150X50)-WD	2438 / 3000 x 150 x 50	45	2
SCL/G/I-(200X50)-WD	2438 / 3000 x 200 x 50	45	2
SCL/G/I-(250X50)-WD	2438 / 3000 x 250 x 50	45	2
SCL/G/I-(300X50)-WD	2438 / 3000 x 300 x 50	45	2
SCL/G/I-(150X75)-WD	2438 / 3000 x 150 x 75	70	2
SCL/G/I-(200X75)-WD	2438 / 3000 x 200 x 75	70	2
SCL/G/I-(250X75)-WD	2438 / 3000 x 250 x 75	70	2
SCL/G/I-(300X75)-WD	2438 / 3000 x 300 x 75	70	2
SCL/G/I-(450X75)-WD	2438 / 3000 x 450 x 75	70	2
SCL/G/I-(600X75)-WD	2438 / 3000 x 600 x 75	70	2
SCL/G/I-(900X75)-WD	2438 / 3000 x 900 x 75	70	2
SCL/G/I-(150X100)-WD	2438 / 3000 x 150 x 100	95	2
SCL/G/I-(200X100)-WD	2438 / 3000 x 200 x 100	95	2
SCL/G/I-(250X100)-WD	2438 / 3000 x 250 x 100	95	2
SCL/G/I-(300X100)-WD	2438 / 3000 x 300 x 100	95	2
SCL/G/I-(400X100)-WD	2438 / 3000 x 400 x 100	95	2
SCL/G/I-(450X100)-WD	2438 / 3000 x 450 x 100	95	2
SCL/G/I-(500X100)-WD	2438 / 3000 x 500 x 100	95	2
SCL/G/I-(600X100)-WD	2438 / 3000 x 600 x 100	95	2
SCL/G/I-(750X100)-WD	2438 / 3000 x 750 x 100	95	2
SCL/G/I-(900X100)-WD	2438 / 3000 x 900 x 100	95	2
SCL/G/I-(1000X100)-WD	2438 / 3000 x 1000 x 100	95	2
SCL/G/I-(200X125)-WD	2438 / 3000 x 200 x 125	120	2
SCL/G/I-(250X125)-WD	2438 / 3000 x 250 x 125	120	2
SCL/G/I-(300X125)-WD	2438 / 3000 x 300 x 125	120	2
SCL/G/I-(400X125)-WD	2438 / 3000 x 400 x 125	120	2
SCL/G/I-(450X125)-WD	2438 / 3000 x 450 x 125	120	2
SCL/G/I-(500X125)-WD	2438 / 3000 x 500 x 125	120	2
SCL/G/I-(600X125)-WD	2438 / 3000 x 600 x 125	120	2
SCL/G/I-(750X125)-WD	2438 / 3000 x 750 x 125	120	2
SCL/G/I-(900X125)-WD	2438 / 3000 x 900 x 125	120	2
SCL/G/I-(1000X125)-WD	2438 / 3000 x 1000 x 125	120	2
SCL/G/I-(200X150)-WD	2438 / 3000 x 200 x 150	145	2
SCL/G/I-(250X150)-WD	2438 / 3000 x 250 x 150	145	2
SCL/G/I-(300X150)-WD	2438 / 3000 x 300 x 150	145	2
SCL/G/I-(400X150)-WD	2438 / 3000 x 400 x 150	145	2
SCL/G/I-(450X150)-WD	2438 / 3000 x 450 x 150	145	2
SCL/G/I-(500X150)-WD	2438 / 3000 x 500 x 150	145	2
SCL/G/I-(600X150)-WD	2438 / 3000 x 600 x 150	145	2
SCL/G/I-(750X150)-WD	2438 / 3000 x 750 x 150	145	2
SCL/G/I-(900X150)-WD	2438 / 3000 x 900 x 150	145	2
SCL/G/I-(1000X150)-WD	2438 / 3000 x 1000 x 150	145	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

Cable Ladder System

Cable Ladder Straight "Type G - Inner" (Welded / Knock Down)

Dimension in Millimeter (mm)

L : Length
W : Width
H : Height

Cable Ladder "Type G - Inner" - Knock Down (KD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/G/I-(150X50)-KD	2438 / 3000 x 150 x 50	45	2
SCL/G/I-(200X50)-KD	2438 / 3000 x 200 x 50	45	2
SCL/G/I-(250X50)-KD	2438 / 3000 x 250 x 50	45	2
SCL/G/I-(300X50)-KD	2438 / 3000 x 300 x 50	45	2
SCL/G/I-(150X75)-KD	2438 / 3000 x 150 x 75	70	2
SCL/G/I-(200X75)-KD	2438 / 3000 x 200 x 75	70	2
SCL/G/I-(250X75)-KD	2438 / 3000 x 250 x 75	70	2
SCL/G/I-(300X75)-KD	2438 / 3000 x 300 x 75	70	2
SCL/G/I-(450X75)-KD	2438 / 3000 x 450 x 75	70	2
SCL/G/I-(600X75)-KD	2438 / 3000 x 600 x 75	70	2
SCL/G/I-(900X75)-KD	2438 / 3000 x 900 x 75	70	2
SCL/G/I-(150X100)-KD	2438 / 3000 x 150 x 100	95	2
SCL/G/I-(200X100)-KD	2438 / 3000 x 200 x 100	95	2
SCL/G/I-(250X100)-KD	2438 / 3000 x 250 x 100	95	2
SCL/G/I-(300X100)-KD	2438 / 3000 x 300 x 100	95	2
SCL/G/I-(400X100)-KD	2438 / 3000 x 400 x 100	95	2
SCL/G/I-(450X100)-KD	2438 / 3000 x 450 x 100	95	2
SCL/G/I-(500X100)-KD	2438 / 3000 x 500 x 100	95	2
SCL/G/I-(600X100)-KD	2438 / 3000 x 600 x 100	95	2
SCL/G/I-(750X100)-KD	2438 / 3000 x 750 x 100	95	2
SCL/G/I-(900X100)-KD	2438 / 3000 x 900 x 100	95	2
SCL/G/I-(1000X100)-KD	2438 / 3000 x 1000 x 100	95	2
SCL/G/I-(200X125)-KD	2438 / 3000 x 200 x 125	120	2
SCL/G/I-(250X125)-KD	2438 / 3000 x 250 x 125	120	2
SCL/G/I-(300X125)-KD	2438 / 3000 x 300 x 125	120	2
SCL/G/I-(400X125)-KD	2438 / 3000 x 400 x 125	120	2
SCL/G/I-(450X125)-KD	2438 / 3000 x 450 x 125	120	2
SCL/G/I-(500X125)-KD	2438 / 3000 x 500 x 125	120	2
SCL/G/I-(600X125)-KD	2438 / 3000 x 600 x 125	120	2
SCL/G/I-(750X125)-KD	2438 / 3000 x 750 x 125	120	2
SCL/G/I-(900X125)-KD	2438 / 3000 x 900 x 125	120	2
SCL/G/I-(1000X125)-KD	2438 / 3000 x 1000 x 125	120	2
SCL/G/I-(200X150)-KD	2438 / 3000 x 200 x 150	145	2
SCL/G/I-(250X150)-KD	2438 / 3000 x 250 x 150	145	2
SCL/G/I-(300X150)-KD	2438 / 3000 x 300 x 150	145	2
SCL/G/I-(400X150)-KD	2438 / 3000 x 400 x 150	145	2
SCL/G/I-(450X150)-KD	2438 / 3000 x 450 x 150	145	2
SCL/G/I-(500X150)-KD	2438 / 3000 x 500 x 150	145	2
SCL/G/I-(600X150)-KD	2438 / 3000 x 600 x 150	145	2
SCL/G/I-(750X150)-KD	2438 / 3000 x 750 x 150	145	2
SCL/G/I-(900X150)-KD	2438 / 3000 x 900 x 150	145	2
SCL/G/I-(1000X150)-KD	2438 / 3000 x 1000 x 150	145	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

◄ Flatwise Equal/Unequal Cross

SCL/G/I/WD AC-1
SCL/G/I/KD AC-1

Flatwise Equal/Unequal Tee ►

SCL/G/I/WD AC-2
SCL/G/I/KD AC-2

◄ Righthand Reducer

SCL/G/I/WD AC-3
SCL/G/I/KD AC-3

Lefthand Reducer ►

SCL/G/I/WD AC-4
SCL/G/I/KD AC-4

**Other design and sizes are available upon request.

"Type G - Inner" - WD/KD

◄ **Straight Reducer**
SCL/G/I/WD AC-5
SCL/G/I/KD AC-5

Flatwise Elbow ►
SCL/G/I/WD AC-6
SCL/G/I/KD AC-6

◄ **Edgewise Elbow Left**
SCL/G/I/WD AC-7
SCL/G/I/KD AC-7

Edgewise Elbow Right ►
SCL/G/I/WD AC-8
SCL/G/I/KD AC-8

**Other design and sizes are available upon request.

"Type G - Inner" - WD/KD

Optional Accessories

Vertical Adjustable Join

"Type G - Outer "

Cable Ladder "Type G - Outer" - Welded (WD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/G/O-(150X50)-WD	2438 / 3000 x 150 x 50	45	2
SCL/G/O-(200X50)-WD	2438 / 3000 x 200 x 50	45	2
SCL/G/O-(250X50)-WD	2438 / 3000 x 250 x 50	45	2
SCL/G/O-(300X50)-WD	2438 / 3000 x 300 x 50	45	2
SCL/G/O-(150X75)-WD	2438 / 3000 x 150 x 75	70	2
SCL/G/O-(200X75)-WD	2438 / 3000 x 200 x 75	70	2
SCL/G/O-(250X75)-WD	2438 / 3000 x 250 x 75	70	2
SCL/G/O-(300X75)-WD	2438 / 3000 x 300 x 75	70	2
SCL/G/O-(450X75)-WD	2438 / 3000 x 450 x 75	70	2
SCL/G/O-(600X75)-WD	2438 / 3000 x 600 x 75	70	2
SCL/G/O-(900X75)-WD	2438 / 3000 x 900 x 75	70	2
SCL/G/O-(150X100)-WD	2438 / 3000 x 150 x 100	95	2
SCL/G/O-(200X100)-WD	2438 / 3000 x 200 x 100	95	2
SCL/G/O-(250X100)-WD	2438 / 3000 x 250 x 100	95	2
SCL/G/O-(300X100)-WD	2438 / 3000 x 300 x 100	95	2
SCL/G/O-(400X100)-WD	2438 / 3000 x 400 x 100	95	2
SCL/G/O-(450X100)-WD	2438 / 3000 x 450 x 100	95	2
SCL/G/O-(500X100)-WD	2438 / 3000 x 500 x 100	95	2
SCL/G/O-(600X100)-WD	2438 / 3000 x 600 x 100	95	2
SCL/G/O-(750X100)-WD	2438 / 3000 x 750 x 100	95	2
SCL/G/O-(900X100)-WD	2438 / 3000 x 900 x 100	95	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

Cable Ladder System

Cable Ladder Straight "Type G - Outer" (Welded)

Dimension in Millimeter (mm)

L : Length
W : Width
H : Height

Cable Ladder "Type G - Outer" - Welded (WD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/G/O-(1000X100)-WD	2438 / 3000 x 1000 x 100	95	2
SCL/G/O-(200X125)-WD	2438 / 3000 x 200 x 125	120	2
SCL/G/O-(250X125)-WD	2438 / 3000 x 250 x 125	120	2
SCL/G/O-(300X125)-WD	2438 / 3000 x 300 x 125	120	2
SCL/G/O-(400X125)-WD	2438 / 3000 x 400 x 125	120	2
SCL/G/O-(450X125)-WD	2438 / 3000 x 450 x 125	120	2
SCL/G/O-(500X125)-WD	2438 / 3000 x 500 x 125	120	2
SCL/G/O-(600X125)-WD	2438 / 3000 x 600 x 125	120	2
SCL/G/O-(750X125)-WD	2438 / 3000 x 750 x 125	120	2
SCL/G/O-(900X125)-WD	2438 / 3000 x 900 x 125	120	2
SCL/G/O-(1000X125)-WD	2438 / 3000 x 1000 x 125	120	2
SCL/G/O-(200X150)-WD	2438 / 3000 x 200 x 150	145	2
SCL/G/O-(250X150)-WD	2438 / 3000 x 250 x 150	145	2
SCL/G/O-(300X150)-WD	2438 / 3000 x 300 x 150	145	2
SCL/G/O-(400X150)-WD	2438 / 3000 x 400 x 150	145	2
SCL/G/O-(450X150)-WD	2438 / 3000 x 450 x 150	145	2
SCL/G/O-(500X150)-WD	2438 / 3000 x 500 x 150	145	2
SCL/G/O-(600X150)-WD	2438 / 3000 x 600 x 150	145	2
SCL/G/O-(750X150)-WD	2438 / 3000 x 750 x 150	145	2
SCL/G/O-(900X150)-WD	2438 / 3000 x 900 x 150	145	2
SCL/G/O-(1000X150)-WD	2438 / 3000 x 1000 x 150	145	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

◄ Flatwise Equal/Unequal Cross

SCL/G/O/WD AC-1

Welded
(WD)

Flatwise Equal/Unequal Tee ►

SCL/G/O/WD AC-2

◄ Righthand Reducer

SCL/G/O/WD AC-3

Welded
(WD)

Lefthand Reducer ►

SCL/G/O/WD AC-4

**Other design and sizes are available upon request.

"Type G - Outer" - WD

◄ **Straight Reducer**
SCL/G/O/WD AC-5

Welded
(WD)

Flatwise Elbow ►
SCL/G/O/WD AC-6

◄ **Edgewise Elbow Left**
SCL/G/O/WD AC-7

Welded
(WD)

Edgewise Elbow Right ►
SCL/G/O/WD AC-8

"Type G - Outer" - WD

**Other design and sizes are available upon request.

Optional Accessories

Vertical Adjustable Join

"Type C - Inner "

Cable Ladder "Type C - Inner" - Welded (WD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/C/I-(150X50)-WD	2438 / 3000 x 150 x 50	45	2
SCL/C/I-(200X50)-WD	2438 / 3000 x 200 x 50	45	2
SCL/C/I-(250X50)-WD	2438 / 3000 x 250 x 50	45	2
SCL/C/I-(300X50)-WD	2438 / 3000 x 300 x 50	45	2
SCL/C/I-(150X75)-WD	2438 / 3000 x 150 x 75	70	2
SCL/C/I-(200X75)-WD	2438 / 3000 x 200 x 75	70	2
SCL/C/I-(250X75)-WD	2438 / 3000 x 250 x 75	70	2
SCL/C/I-(300X75)-WD	2438 / 3000 x 300 x 75	70	2
SCL/C/I-(450X75)-WD	2438 / 3000 x 450 x 75	70	2
SCL/C/I-(600X75)-WD	2438 / 3000 x 600 x 75	70	2
SCL/C/I-(900X75)-WD	2438 / 3000 x 900 x 75	70	2
SCL/C/I-(150X100)-WD	2438 / 3000 x 150 x 100	95	2
SCL/C/I-(200X100)-WD	2438 / 3000 x 200 x 100	95	2
SCL/C/I-(250X100)-WD	2438 / 3000 x 250 x 100	95	2
SCL/C/I-(300X100)-WD	2438 / 3000 x 300 x 100	95	2
SCL/C/I-(400X100)-WD	2438 / 3000 x 400 x 100	95	2
SCL/C/I-(450X100)-WD	2438 / 3000 x 450 x 100	95	2
SCL/C/I-(500X100)-WD	2438 / 3000 x 500 x 100	95	2
SCL/C/I-(600X100)-WD	2438 / 3000 x 600 x 100	95	2
SCL/C/I-(750X100)-WD	2438 / 3000 x 750 x 100	95	2
SCL/C/I-(900X100)-WD	2438 / 3000 x 900 x 100	95	2
SCL/C/I-(1000X100)-WD	2438 / 3000 x 1000 x 100	95	2
SCL/C/I-(200X125)-WD	2438 / 3000 x 200 x 125	120	2
SCL/C/I-(250X125)-WD	2438 / 3000 x 250 x 125	120	2
SCL/C/I-(300X125)-WD	2438 / 3000 x 300 x 125	120	2
SCL/C/I-(400X125)-WD	2438 / 3000 x 400 x 125	120	2
SCL/C/I-(450X125)-WD	2438 / 3000 x 450 x 125	120	2
SCL/C/I-(500X125)-WD	2438 / 3000 x 500 x 125	120	2
SCL/C/I-(600X125)-WD	2438 / 3000 x 600 x 125	120	2
SCL/C/I-(750X125)-WD	2438 / 3000 x 750 x 125	120	2
SCL/C/I-(900X125)-WD	2438 / 3000 x 900 x 125	120	2
SCL/C/I-(1000X125)-WD	2438 / 3000 x 1000 x 125	120	2
SCL/C/I-(200X150)-WD	2438 / 3000 x 200 x 150	145	2
SCL/C/I-(250X150)-WD	2438 / 3000 x 250 x 150	145	2
SCL/C/I-(300X150)-WD	2438 / 3000 x 300 x 150	145	2
SCL/C/I-(400X150)-WD	2438 / 3000 x 400 x 150	145	2
SCL/C/I-(450X150)-WD	2438 / 3000 x 450 x 150	145	2
SCL/C/I-(500X150)-WD	2438 / 3000 x 500 x 150	145	2
SCL/C/I-(600X150)-WD	2438 / 3000 x 600 x 150	145	2
SCL/C/I-(750X150)-WD	2438 / 3000 x 750 x 150	145	2
SCL/C/I-(900X150)-WD	2438 / 3000 x 900 x 150	145	2
SCL/C/I-(1000X150)-WD	2438 / 3000 x 1000 x 150	145	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

Cable Ladder System

Cable Ladder Straight "Type C -Inner" (Welded / Knock Down)

Dimension in Millimeter (mm)

L : Length
W : Width
H : Height

Cable Ladder "Type C - Inner" - Knock Down (KD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/C/I-(150X50)-KD	2438 / 3000 x 150 x 50	45	2
SCL/C/I-(200X50)-KD	2438 / 3000 x 200 x 50	45	2
SCL/C/I-(250X50)-KD	2438 / 3000 x 250 x 50	45	2
SCL/C/I-(300X50)-KD	2438 / 3000 x 300 x 50	45	2
SCL/C/I-(150X75)-KD	2438 / 3000 x 150 x 75	70	2
SCL/C/I-(200X75)-KD	2438 / 3000 x 200 x 75	70	2
SCL/C/I-(250X75)-KD	2438 / 3000 x 250 x 75	70	2
SCL/C/I-(300X75)-KD	2438 / 3000 x 300 x 75	70	2
SCL/C/I-(450X75)-KD	2438 / 3000 x 450 x 75	70	2
SCL/C/I-(600X75)-KD	2438 / 3000 x 600 x 75	70	2
SCL/C/I-(900X75)-KD	2438 / 3000 x 900 x 75	70	2
SCL/C/I-(150X100)-KD	2438 / 3000 x 150 x 100	95	2
SCL/C/I-(200X100)-KD	2438 / 3000 x 200 x 100	95	2
SCL/C/I-(250X100)-KD	2438 / 3000 x 250 x 100	95	2
SCL/C/I-(300X100)-KD	2438 / 3000 x 300 x 100	95	2
SCL/C/I-(400X100)-KD	2438 / 3000 x 400 x 100	95	2
SCL/C/I-(450X100)-KD	2438 / 3000 x 450 x 100	95	2
SCL/C/I-(500X100)-KD	2438 / 3000 x 500 x 100	95	2
SCL/C/I-(600X100)-KD	2438 / 3000 x 600 x 100	95	2
SCL/C/I-(750X100)-KD	2438 / 3000 x 750 x 100	95	2
SCL/C/I-(900X100)-KD	2438 / 3000 x 900 x 100	95	2
SCL/C/I-(1000X100)-KD	2438 / 3000 x 1000 x 100	95	2
SCL/C/I-(200X125)-KD	2438 / 3000 x 200 x 125	120	2
SCL/C/I-(250X125)-KD	2438 / 3000 x 250 x 125	120	2
SCL/C/I-(300X125)-KD	2438 / 3000 x 300 x 125	120	2
SCL/C/I-(400X125)-KD	2438 / 3000 x 400 x 125	120	2
SCL/C/I-(450X125)-KD	2438 / 3000 x 450 x 125	120	2
SCL/C/I-(500X125)-KD	2438 / 3000 x 500 x 125	120	2
SCL/C/I-(600X125)-KD	2438 / 3000 x 600 x 125	120	2
SCL/C/I-(750X125)-KD	2438 / 3000 x 750 x 125	120	2
SCL/C/I-(900X125)-KD	2438 / 3000 x 900 x 125	120	2
SCL/C/I-(1000X125)-KD	2438 / 3000 x 1000 x 125	120	2
SCL/C/I-(200X150)-KD	2438 / 3000 x 200 x 150	145	2
SCL/C/I-(250X150)-KD	2438 / 3000 x 250 x 150	145	2
SCL/C/I-(300X150)-KD	2438 / 3000 x 300 x 150	145	2
SCL/C/I-(400X150)-KD	2438 / 3000 x 400 x 150	145	2
SCL/C/I-(450X150)-KD	2438 / 3000 x 450 x 150	145	2
SCL/C/I-(500X150)-KD	2438 / 3000 x 500 x 150	145	2
SCL/C/I-(600X150)-KD	2438 / 3000 x 600 x 150	145	2
SCL/C/I-(750X150)-KD	2438 / 3000 x 750 x 150	145	2
SCL/C/I-(900X150)-KD	2438 / 3000 x 900 x 150	145	2
SCL/C/I-(1000X150)-KD	2438 / 3000 x 1000 x 150	145	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

◄ Flatwise Equal/Unequal Cross

SCL/C/I/WD AC-1
SCL/C/I/KD AC-1

Flatwise Equal/Unequal Tee ►

SCL/C/I/WD AC-2
SCL/C/I/KD AC-2

◄ Righthand Reducer

SCL/C/I/WD AC-3
SCL/C/I/KD AC-3

Lefthand Reducer ►

SCL/C/I/WD AC-4
SCL/C/I/KD AC-4

**Other design and sizes are available upon request.

"Type C - Inner" - WD/KD

◄ Straight Reducer
SCL/C/I/WD AC-5
SCL/C/I/KD AC-5

Flatwise Elbow ►
SCL/C/I/WD AC-6
SCL/C/I/KD AC-6

◄ Edgewise Elbow Left
SCL/C/I/WD AC-7
SCL/C/I/KD AC-7

Edgewise Elbow Right ►
SCL/C/I/WD AC-8
SCL/C/I/KD AC-8

"Type C - Inner" - WD/KD

**Other design and sizes are available upon request.

Optional Accessories

Vertical Adjustable Join

"Type C - Outer "

Cable Ladder "Type C - Outer" - Welded (WD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/C/O-(150X50)-WD	2438 / 3000 x 150 x 50	45	2
SCL/C/O-(200X50)-WD	2438 / 3000 x 200 x 50	45	2
SCL/C/O-(250X50)-WD	2438 / 3000 x 250 x 50	45	2
SCL/C/O-(300X50)-WD	2438 / 3000 x 300 x 50	45	2
SCL/C/O-(150X75)-WD	2438 / 3000 x 150 x 75	70	2
SCL/C/O-(200X75)-WD	2438 / 3000 x 200 x 75	70	2
SCL/C/O-(250X75)-WD	2438 / 3000 x 250 x 75	70	2
SCL/C/O-(300X75)-WD	2438 / 3000 x 300 x 75	70	2
SCL/C/O-(450X75)-WD	2438 / 3000 x 450 x 75	70	2
SCL/C/O-(600X75)-WD	2438 / 3000 x 600 x 75	70	2
SCL/C/O-(900X75)-WD	2438 / 3000 x 900 x 75	70	2
SCL/C/O-(150X100)-WD	2438 / 3000 x 150 x 100	95	2
SCL/C/O-(200X100)-WD	2438 / 3000 x 200 x 100	95	2
SCL/C/O-(250X100)-WD	2438 / 3000 x 250 x 100	95	2
SCL/C/O-(300X100)-WD	2438 / 3000 x 300 x 100	95	2
SCL/C/O-(400X100)-WD	2438 / 3000 x 400 x 100	95	2
SCL/C/O-(450X100)-WD	2438 / 3000 x 450 x 100	95	2
SCL/C/O-(500X100)-WD	2438 / 3000 x 500 x 100	95	2
SCL/C/O-(600X100)-WD	2438 / 3000 x 600 x 100	95	2
SCL/C/O-(750X100)-WD	2438 / 3000 x 750 x 100	95	2
SCL/C/O-(900X100)-WD	2438 / 3000 x 900 x 100	95	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

Cable Ladder System

Cable Ladder Straight "Type C - Outer" (Welded)

Dimension in Millimeter (mm)

L : Length
W : Width
H : Height

Cable Ladder "Type C - Outer" - Welded (WD)

Model	Nominal Size (mm)		
	Body (LxWxH)	Splice Plate (H)	Thickness
SCL/C/O-(1000X100)-WD	2438 / 3000 x 1000 x 100	95	2
SCL/C/O-(200X125)-WD	2438 / 3000 x 200 x 125	120	2
SCL/C/O-(250X125)-WD	2438 / 3000 x 250 x 125	120	2
SCL/C/O-(300X125)-WD	2438 / 3000 x 300 x 125	120	2
SCL/C/O-(400X125)-WD	2438 / 3000 x 400 x 125	120	2
SCL/C/O-(450X125)-WD	2438 / 3000 x 450 x 125	120	2
SCL/C/O-(500X125)-WD	2438 / 3000 x 500 x 125	120	2
SCL/C/O-(600X125)-WD	2438 / 3000 x 600 x 125	120	2
SCL/C/O-(750X125)-WD	2438 / 3000 x 750 x 125	120	2
SCL/C/O-(900X125)-WD	2438 / 3000 x 900 x 125	120	2
SCL/C/O-(1000X125)-WD	2438 / 3000 x 1000 x 125	120	2
SCL/C/O-(200X150)-WD	2438 / 3000 x 200 x 150	145	2
SCL/C/O-(250X150)-WD	2438 / 3000 x 250 x 150	145	2
SCL/C/O-(300X150)-WD	2438 / 3000 x 300 x 150	145	2
SCL/C/O-(400X150)-WD	2438 / 3000 x 400 x 150	145	2
SCL/C/O-(450X150)-WD	2438 / 3000 x 450 x 150	145	2
SCL/C/O-(500X150)-WD	2438 / 3000 x 500 x 150	145	2
SCL/C/O-(600X150)-WD	2438 / 3000 x 600 x 150	145	2
SCL/C/O-(750X150)-WD	2438 / 3000 x 750 x 150	145	2
SCL/C/O-(900X150)-WD	2438 / 3000 x 900 x 150	145	2
SCL/C/O-(1000X150)-WD	2438 / 3000 x 1000 x 150	145	2

**Specification subject to change without prior notice.
***Thickness Tolerance with + - 10%

*For order information, please refer page 63.

◄ **Flatwise Equal/Unequal Cross**
SCL/C/O/WD AC-1

Flatwise Equal/Unequal Tee ►
SCL/C/O/WD AC-2

◄ **Righthand Reducer**
SCL/C/O/WD AC-3

Lefthand Reducer ►
SCL/C/O/WD AC-4

**Other design and sizes are available upon request.

"Type C - Outer" - WD

◄ **Straight Reducer**
SCL/C/O/WD AC-5

Welded
(WD)

Flatwise Elbow ►
SCL/C/O/WD AC-6

◄ **Edgewise Elbow Left**
SCL/C/O/WD AC-7

Welded
(WD)

Edgewise Elbow Right ►
SCL/C/O/WD AC-8

"Type C - Outer" - WD

**Other design and sizes are available upon request.